

# 4008ci / 5008ci / 6008ci / 7008ci

## Technical data

### GENERAL

<b>Type</b>	Desktop
<b>Function</b>	Copy, print, scan, optional: fax
<b>Print technology</b>	Laser colour and b/w
<b>Original format</b>	max A3 from platen glass
<b>Copy/print speed</b>	4008ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w 5008ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w 6008ci: max 60 A4 pages/min and max 30 A3 pages/min in colour and b/w 7008ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and b/w
<b>1st page (Print/Copy)</b>	Colour: 6.5/5.9 seconds*, b/w: 5.1/ 4.5 seconds* (4008ci), Colour: 5.4/4.8 seconds*, b/w: 4.3/3.7 seconds* (5008ci), Colour: 5.1/4.4 seconds*, b/w: 3.8/ 3.4 seconds* (6008ci), Colour: 5.0/4.4 seconds*, b/w: 3.7/3.4 seconds* (7008ci)
<b>Warm-up time</b>	17 seconds (4008ci/5008ci/6008ci) 26 seconds (7008ci)
<b>Copy resolution</b>	600 x 600 dpi
<b>Greyscales</b>	256
<b>Paper feed</b>	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
<b>Paper weights</b>	Universal cassette 52-300 g/m <sup>2</sup> , multibypass 52-300 g/m <sup>2</sup> , duplex 64-256 g/m <sup>2</sup>
<b>Paper output</b>	500 sheet A4
<b>System memory</b>	4 GB RAM, 64 GB SSD/optional: 320 GB or 1 TB HDD**
<b>Continuous copying</b>	1-9,999 copies
<b>Zoom</b>	25 % - 400 % in steps of 1 %
<b>Functions</b>	Adjustable capacitive colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), secure boot, run time integrity check, trusted platform modul (TPM), S/MIME etc.

### DIMENSIONS/WEIGHT

<b>Dimensions</b>	790 x 602 x 665 mm (H x W x D)
<b>Weight</b>	approx. 95 kg

### ENVIRONMENT

<b>Mains voltage</b>	220/240 V, 50/60 Hz
<b>Power consumption</b>	approx. 1,750 W (2,400 W - 7008ci) max, approx. 660/780/990/1,140 W in operation (4008ci/5008ci/6008ci/7008ci), approx. 45 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.51/0.63/0.79/1.01 kWh/week (4008ci/5008ci/6008ci/7008ci)
<b>Noise level</b>	4008ci/5008ci/6008ci/7008ci: approx. (50.3/50) (51.9/51.6) (53.4/53) (54.3/54) dB(A) in operation (colour / b/w-mode), stand-by mode: 30.5/30.3/33.3/31.7 dB(A) (ISO 7779/9296)
<b>Safety</b>	GS/TÜV, CE

### PRINT SYSTEM

<b>Type</b>	Integrated within the system
<b>Print format</b>	A6R-SRA3
<b>Print resolution</b>	600 x 600 dpi, max 4,800 equivalent x 1,200 dpi
<b>Processor</b>	ARM A53 1.6GHz
<b>Interfaces</b>	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot
<b>Network protocols</b>	TCP/IP, Net BEUI
<b>Operating systems</b>	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare***, Linux, Mac ex OS 10.9
<b>Emulations</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIc
<b>Functions</b>	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/ Apple AirPrint, NFC, Wi-Fi Direct***

### SCAN SYSTEM

<b>Scan type</b>	CCD colour and b/w
<b>Scan format</b>	max A3
<b>Scan speed</b>	max 137 (simplex) or 274 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)
<b>Scan resolution</b>	200 dpi, 300 dpi, 400 dpi, 600 dpi
<b>Scan mode</b>	Photo, text, photo/text, optimised for OCR
<b>File types</b>	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
<b>Interface</b>	10/100/1000BaseTX
<b>Network protocol</b>	TCP/IP
<b>Operating systems</b>	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Functions</b>	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, Multiple cropping, Handwriting enhancement

### OPTIONAL FAX SYSTEM 12

<b>Compatibility</b>	Super G3
<b>Original format</b>	max A3
<b>Modem speed</b>	33.6 kbps
<b>Transmission speed</b>	3 seconds or less using JBIG
<b>Compression method</b>	JBIG, MMR, MR, MH
<b>Fax resolution</b>	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
<b>Fax memory</b>	170 MB
<b>Abbreviated dial</b>	2,000 numbers
<b>One touch dial</b>	1,000 numbers
<b>Group dial</b>	500 numbers
<b>Operating systems</b>	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
<b>Functions</b>	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

### OPTIONS

<b>Original feeder</b>	DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m <sup>2</sup> ), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m <sup>2</sup> ), DP-7170 document processor with simultaneous duplex scanning and multi-feed detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m <sup>2</sup> )
<b>Platen cover</b>	Platen cover type E (if document processor is not installed)
<b>Finisher</b>	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7008ci), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7140 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7150 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7140 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 Inserter (available for 6008ci/7008ci), ZF-7100 Z-fold unit (available for 6008ci/7008ci)
<b>Job Separator</b>	JS-7100 (100 sheet, 52-300 g/m <sup>2</sup> , A6R-SRA3), JS-7110 inner shift tray (250 sheet, 52-300 g/m <sup>2</sup> , A6R-SRA3)
<b>Paper feed</b>	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
<b>Other options</b>	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 Thin-Print® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card (IEEE802.11b/g/n), IB-37 WLAN card (IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card**** (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD**), HD-16 (1 TB HDD**), Fiery® Controller (Printing System 17)

\* Depending on operating status

\*\* For copy, print, scan, fax

\*\*\* optional

\*\*\*\* IB-38 is only available for selected countries outside the EU that do not support the IB-37



Specifications subject to change without notice.

Image shows machine with optional accessories.



TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler