

Technical Data:

P-C3563DN • P-C4063DN • P458ci

GENERAL		DIMENSIONS/WEIGHT		OPTIONS	
Type	Desktop	Dimensions	P-C3563DN: 392,5 x 394 x 533 mm (H x W x D) P-C4063DN: 455 x 394 x 533 mm (H x W x D) P458ci: 455 x 394 x 533 mm (H x W x D)	Paper feed	P-C3563DN/P-C4063DN: max 3x PF-5150 (550 sheet universal cassette [A6-A4, 60-220 g/m ²]) P458ci: max 4x PF-5150 (550 sheet universal cassette [A6-A4, 60-220 g/m ²])
Function	Print	Weight	P-C3563DN: approx. 33 kg P-C4063DN/P458ci: approx. 34 kg	Other options	Card authentication kit (B), Card reader holder 12, UG-33 ThinPrint® kit, UG-35 Trusted Platform Module 2.0, IB-50 Gigabit Ethernet card, IB-37 WLAN card (IEEE802.11b/g/n), IB-37 WLAN card (IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card ⁵ (IEEE 802.11 b/g/n Wi-Fi direct), HD-17 SSD memory (64 GB), HD-18 SSD memory (256 GB), HD-19 SSD memory (512 GB), M-DDR III 1 GB/2 GB memory B, cabinet no. 82 (high), cabinet no. 83 (low)
Print technology	Laser colour and b/w	ENVIRONMENT			
print speed	P-C3563DN: max 35 A4 pages/min, duplex: max 17.5 A4 pages/min in colour and b/w P-C4063DN: max 40 A4 pages/min, duplex: max 20 A4 pages/min in colour and b/w P458ci: max 45 A4 pages/min, duplex: max 37 A4 pages/min in colour and b/w	Mains voltage	220/240 V, 50(60 Hz)		
1st page¹	P-C3563DN: 7.0 sec (colour), 5.7 sec (b/w) P-C4063DN: 6.6 sec (colour), 5.4 sec (b/w) P458ci: 6.2 sec (colour), 5.1 sec (b/w)	Power consumption	P-C3563DN/P-C4063DN/P458ci: approx. 1,278/1,298/TBD W max, approx. 377/454/TBD W in operation, approx. 12/12/TBD W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.32/0.37/0.42 kWh/week		
Warm-up time	P-C3563DN: 23 sec ¹ P-C4063DN: 21 sec ¹ P458ci: 20 sec ¹	Noise level	Colour: approx. 50/51.5/TBD dB(A) in operation, b/w: approx. 49.5/51.3/TBD dB(A) in operation, not measurable in stand-by mode (ISO 7779/9296)		
Copy resolution	600 x 600 dpi	Safety	GS/TÜV, CE		
Greyscale	256	PRINT SYSTEM			
Paper feed	1 x 550 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm])	Type	Integrated within the system		
Paper weights	Universal cassette 60-220 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ²	Print format	A6R-A4		
Paper output	P-C3563DN: 250 sheets A4 P-C4063DN/P458ci: 500 sheets A4	Print resolution	600 x 600 dpi, max. 1,200 x 1,200 dpi (reduced speed)		
System memory	P-C3563DN: 1 GB RAM P-C4063DN/P458ci: 1 GB RAM (max. 3 GB RAM) 64/256/512 GB SSD memory ²	Processor	ARM Cortex-A9 dual core 1.2 GHz + ARM Cortex-M3 100 MHz		
Display	P-C3563DN/P-C4063DN: Adjustable (90°) LCD display 128 x 64 dots, half size 21 characters x 5 lines with numeric keypad P458ci: Adjustable (90°) colour touch screen (4.3 inch) with numeric keypad	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), SD-card slot, Wi-Fi ²		
Functions	Duplex, job reservation, job programs, N-up-printing, login by function, 100 management codes, encryption/overwriting of hard disk data (Data Security Kit) in combination with optional SSD memory, Secure Boot ³ , Runtime Integrity Check ³ , Simple Certificate Enrollment Protocol (SCEP), TLS 1.3, OCSP, CRL ⁴ , SIEM-Support etc.	Network protocols	TCP/IP, Net BEUI		
		Operating systems	Windows 8/8.1/10/11, Server 2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14		
		Emulations	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS		
		Functions	Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, ECO-print, Mobile Print (Android/iOS), Apple AirPrint, Universal print, Wi-Fi ²		

- ¹ depending on operating status
- ² optional
- ³ UG-35 Trusted Platform Modul necessary
- ⁴ optional SD card or SSD required (CRL not available for P-C3563DN)
- ⁵ country specific








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.




TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler