

# P-C3062DN / P-C3562DN / P-C4072DN

## Technical data

General		General		Environment	
<b>Type</b>	Desktop	<b>Network protocols</b>	TCP/IP, NetBEUI	<b>Noise level</b>	<i>P-C3062DN:</i> approx. 50.2 dB(A) in operation, approx. 30.2 dB(A) in stand-by mode (ISO 7779/9296) <i>P-C3562DN:</i> approx. 52.0 dB(A) in operation, approx. 30.1 dB(A) in stand-by mode (ISO 7779/9296) <i>P-C4072DN:</i> approx. 52.7 dB(A) in operation, approx. 29.5 dB(A) in stand-by mode (ISO 7779/9296)
<b>Function</b>	Print	<b>Operating systems</b>	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016, Novell NetWare**, Linux, Mac OS 10.5	<b>Safety</b>	GS/TÜV, CE
<b>Print technology</b>	Laser colour and b/w	<b>Emulations</b>	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	<b>Options</b>	
<b>Print format</b>	max A4	<b>Functions</b>	Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS), Apple AirPrint**, Google Cloud Print, Wi-Fi**	<b>Paper feed</b>	max 3 x PF-5100 (500 sheet universal cassette [A5R-A4, 60-220 g/m <sup>2</sup> ])
<b>Print speed</b>	<i>P-C3062DN:</i> max 30 A4 pages/min in colour and b/w, duplex: max 15 A4 pages/min in colour and b/w <i>P-C3562DN:</i> max 35 A4 pages/min in colour and b/w, duplex: max 32 A4 pages/min in colour and b/w <i>P-C4072DN:</i> max 40 A4 pages/min in colour and b/w, duplex: max 36 A4 pages/min in colour and b/w	<b>Dimensions/Weight</b>		<b>Other options</b>	Data security kit (E), Card authentication kit (B), UG-33 ThinPrint® kit, IB-50 Gigabit Ethernet card, IB-36 or IB-51 WLAN card, HD-6 SSD (32 GB), HD-7 SSD (128 GB), cabinet no. 72 (high), cabinet no. 73 (low)
<b>1st page</b>	<i>P-C3062DN:</i> Colour: 7 seconds*, b/w: 6 seconds* <i>P-C3562DN:</i> Colour: 7.5 seconds*, b/w: 6.5 seconds* <i>P-C4072DN:</i> Colour: 6.5 seconds*, b/w: 5.5 seconds*	<b>Dimensions</b>	<i>P-C3062DN:</i> 409.5 x 390 x 532 mm (H x W x D) <i>P-C3562DN/P-C4072DN:</i> 469.5 x 390 x 532 mm (H x W x D)	<b>*Depending on operating status.</b>	
<b>Warm-up time</b>	<i>P-C3062DN:</i> 26 seconds* <i>P-C3562DN:</i> 25 seconds* <i>P-C4072DN:</i> 24 seconds*	<b>Weight</b>	<i>P-C3062DN:</i> approx. 28.3 kg <i>P-C3562DN:</i> approx. 29.5 kg <i>P-C4072DN:</i> approx. 31 kg	<b>**optional</b>	
<b>Print resolution</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)	<b>Environment</b>		<b>Specifications subject to change without notice.</b>	
<b>Greyscales</b>	256	<b>Mains voltage</b>	220/240 V, 50 Hz	<b>Image shows machine with optional accessories.</b>	
<b>Paper feed</b>	1 x 500 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4)	<b>Power consumption</b>	<i>P-C3062DN:</i> approx. 1,113 W max, approx. 452 W in operation, approx. 56 W in stand-by mode, approx. 0.6 W in sleep mode, TEC value: 0.42 KWh/week <i>P-C3562DN:</i> approx. 1,297 W max, approx. 510 W in operation, approx. 74 W in stand-by mode, approx. 0.6 W in sleep mode, TEC value: 0.49 KWh/week <i>P-C4072DN:</i> approx. 1,340 W max, approx. 623 W in operation, approx. 77 W in stand-by mode, approx. 0.6 W in sleep mode, TEC value: 0.56 KWh/week		
<b>Paper weights</b>	Universal cassette 60-163 g/m <sup>2</sup> , multi-bypass 60-220 g/m <sup>2</sup> , duplex 60-163 g/m <sup>2</sup>				
<b>Paper output</b>	<i>P-C3062DN:</i> 250 sheet A4 <i>P-C3562DN/P-C4072DN:</i> 500 sheet A4				
<b>System memory</b>	<i>P-C3062DN:</i> 1,024 MB RAM, max 1,024 MB RAM, 32/128 GB hard disk** <i>P-C3562DN/P-C4072DN:</i> 1,024 MB RAM, max 3,072 MB RAM, 32/128 GB hard disk**				
<b>Processor</b>	ARM Cortex-A9 dual core, 1.2 GHz				
<b>Interfaces</b>	USB 2.0, 10/100/1000BaseTX, USB-host (2), Wi-Fi**				

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

[www.triumph-adler.com](http://www.triumph-adler.com)

