

Technical Data:

P-4532i MFP • P-4539i MFP • P-5539i MFP • P-6039i MFP

GENERAL

| | |
|-------------------------------|--|
| Type | Desktop |
| Function | P-4532i MFP: Copy, print, scan P-4539i MFP/P-5539i MFP/P-6039i MFP: Copy, print, scan, fax |
| Print technology | Laser b/w |
| Original format | max A4 from platen glass |
| Original feeder | P-4532i/P-4539i MFP: 75 sheet document processor with automatic reverse function, A6R-A4, 50-120 g/m ² (standard) P-5539i/P-6039i* MFP: 100 sheet document processor with simultaneous duplex scanning and *double feed prevention sensor, A6R-A4, 50-120 g/m ² (standard) |
| Copy/print speed | P-4532i/P-4539i MFP: max 45 A4 pages/min, duplex: max 22.5 A4 pages/min P-5539i MFP: max 55 A4 pages/min, duplex: max 39.5 A4 pages/min P-6039i MFP: max 60 A4 pages/min, duplex: max 43 A4 pages/min |
| 1st page (print/copy)* | 5.3/6 seconds (P-4532i/P-4539i MFP) / 4.5/6 seconds (P-5539i/P-6039i MFP) |
| Warm-up time | 23 seconds (P-4532i/P-4539i MFP) / 25 seconds (P-5539i/P-6039i MFP) |
| Copy resolution | 600 x 600 dpi |
| Greyscales | 256 |
| Paper feed | P-4532i/P-4539i MFP: 1 x 500 sheet universal cassette (A5R-A4, min 140 x 210 mm, max 216 x 356 mm) P-5539i/P-6039i MFP: 1 x 500 sheet universal cassette (A6R-A4, min 105 x 148 mm, max 216 x 356 mm); 100 sheet multi-bypass (A6R-A4 [min 70 x 139.7 mm, max 216 x 356 mm]), banner length: max 915 mm |
| Paper weights | Universal cassette 60-120 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-120 g/m ² |
| Paper output | P-4532i/P-4539i MFP: 250 sheet A4 (face-down) P-5539i/P-6039i MFP: 500 sheet A4 (face-down), 250 sheet A4 (face-up with optional PT-320) |
| System memory | 1.5 GB RAM, (max 3.5 GB RAM), 64/256/512 GB SSD** |
| Continuous copying | 1-999 copies |
| Zoom | 25 % - 400 % in steps of 1 % |
| Functions | Colour touch screen (7 inch), duplex, job reservation, favourites (programs), ID card copy, scan once - copy many, continuous scan, skip blank pages, N-up, quiet mode (half speed mode), 100 management codes, Data Security Kit, Secure Boot, Runtime Integrity Check, etc. |

DIMENSIONS/WEIGHT

| | |
|-------------------|---|
| Dimensions | P-4532i/P-4539i MFP: 575 x 475 x 476 mm (H x W x D), P-5539i MFP: 590 x 480 x 495 mm (H x W x D), P-6039i MFP: 610 x 480 x 495 mm (H x W x D) |
| Weight | P-4532i/P-4539i MFP: approx. 22.5 kg, P-5539i MFP: 24.1/P-6039i MFP: approx. 24.5 kg |

ENVIRONMENT

| | |
|--------------------------|---|
| Mains voltage | 220/240 V, 50/60 Hz |
| Power consumption | P-4532i/P-4539i MFP: approx. 1,270 W max, approx. 599/564 W in operation, approx. 57/56 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.62 KWh/week P-5539i MFP/P-6039i MFP: approx. 1,287/1,309 W max, approx. 704/741 W in operation, approx. 60/58 W in stand-by mode, approx. 0.6/0.5 W in sleep mode, TEC value: 0.78/0.84 KWh/week |
| Noise level | P-4532 MFP/P-4539 MFP: approx. 52.6 dB(A) in operation, approx. 22.0 dB(A) in stand-by mode (DIN ISO 7779/9296) P-5539i MFP/P-6039i MFP: approx. 54.5/56.0 dB(A) in operation, approx. 23.3/22.7 dB(A) in stand-by mode (DIN ISO 7779/9296) |
| Safety | GS/TÜV, CE |

PRINT SYSTEM

| | |
|--------------------------|--|
| Type | Integrated within the system |
| Print format | A6R-A4 |
| Print resolution | 1,200 x 1,200 dpi |
| Processor | ARM Cortex-A53 Dual Core, 1.4 GHz |
| Interfaces | USB 2.0, 10/100/1000BaseTX, USB host |
| Network protocols | TCP/IP, Net BEUI |
| Operating systems | Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14 |
| Emulations | PCL6 (PCL 5e/c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, XPS, Open XPS, PDF 1.7 |
| Functions | USB direct printing, printing of e-mails, proof & hold, private printing, barcode printing, WSD/internet printing; Mobile Print/Apple AirPrint**, Wi-Fi**, Microsoft Universal Print |

SCAN SYSTEM

| | |
|--------------------|---|
| Scan type | CCD colour and b/w |
| Scan format | max A4 |
| Scan speed | P-4532i/P-4539i MFP: b/w: max 60/26 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 40/17 A4 originals/min (simplex/duplex) with 300 dpi P-5539i MFP/P-6039i MFP: b/w: max 60/120 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 40/80 A4 originals/min (simplex/duplex) with 300 dpi |

| | |
|--------------------------|--|
| Scan resolution | 200 dpi, 300 dpi, 400 dpi, 600 dpi |
| Scan mode | Photo, text, photo/text, optimised for OCR |
| File types | TIFF, JPEG, PDF, PDF/A-1a, PDF/A-1b, PDF/A-2a, PDF/A-2b, PDF/A-2u, high compression PDF, encrypted PDF, XPS, Open XPS, MS Office/text-searchable PDF** |
| Interfaces | 10/100/1000BaseTX, USB 2.0 |
| Network protocol | TCP/IP |
| Operating systems | Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022 |
| Functions | Scan to SMB, Scan to e-mail, Scan to FTP, Scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, Multi Crop function*** |

FAX SYSTEM (P-4539i MFP - P-5539i MFP - P-6039i MFP)

| | |
|---------------------------|--|
| Compatibility | Super G3 |
| Original format | max A4 |
| Modem speed | 33.6 kbps |
| Transmission speed | 3 seconds or less using JBIG |
| Compression method | JBIG, MMR, MR, MH |
| Fax resolution | Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi) |
| Fax memory | 8 MB (3.5 MB image memory) |
| Abbreviated dial | 200 numbers |
| One touch dial | 100 numbers |
| Group dial | 50 numbers |
| Operating systems | Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016 |
| Functions | Network fax driver, automatic redialling, delayed transmission |

OPTIONS

| | |
|----------------------|--|
| Paper feed | max 4 x PF-3110 (500 sheet universal cassettes [A5R-A4, 60-120 g/m ²]) |
| Other options | PT-320 output tray (250 sheet face-up, only for P-5539i MFP/P-6039i MFP), Scan Extension Kit (A)***, Card Authentication Kit (B), Card Reader Holder (10), UG-33 ThinPrint® Kit, UG-50 (Trusted Platform Module), IB-50 Gigabit Ethernet card, IB-37 (5 GHz) or IB-38 (2.4 GHz)*** WLAN card, HD-17 SSD (64 GB), HD-18 SSD (256 GB), HD-19 SSD (512 GB), MM-20 (1 GB DIMM), MM-21 (2 GB DIMM), MS-5100 B manual stapler for 20 sheet (only for P-5539i MFP/P-6039i MFP), cabinet no. 79 (high), cabinet no. 80 (low), CA-3100 Caster Kit |

* depending on operating status
** optional
*** additional memory required
**** country specific








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.




TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler