

P-3521 MFP / P-3527w MFP

Technical data

| General | | Environment | | Faxsystem (P-3527w MFP only) | |
|---------------------------|--|--------------------------|--|------------------------------|--|
| Type | Desktop | Noise level | approx. 47.2 dB(A), stand-by mode: immeasurable (DIN/ISO 7779/9296) | Compatibility | Super G3 |
| Function | <i>P-3521 MFP:</i> Copy, print, scan <i>P-3527w MFP:</i> Copy, print, scan, fax | Safety | GS/TÜV, CE | Original format | max A4 |
| Print technology | Laser b/w | Print system | | Modem speed | 33.6 kbps |
| Original format | max A4 from platen glass | Type | Integrated within the system | Transmission speed | 3 seconds or less using JBIG |
| Original feeder | 50 sheet A4 (standard, A6R-A4), 50-160 g/m ² | Print format | A6R-A4 | Compression method | JBIG, MMR, MR, MH |
| Copy/print speed | max 35 A4 pages/min, duplex: max 17.5 A4 pages/min | Print resolution | 600 x 600 dpi, 1,200 x 1,200 dpi | Fax resolution | Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi) |
| 1st page | 6.9 seconds (copy)* / 6.8 seconds (print)* | Processor | Cortex-A9, 800 MHz | Fax memory | 3.5 MB image buffer |
| Warm-up time | <i>P-3521 MFP:</i> 17 seconds <i>P-3527w MFP:</i> 20 seconds | Interfaces | USB 2.0, 10/100/1000BaseTX, USB-Host, SD slot, Wi-Fi (P-3527 w MFP only) | Abbreviated dial | 200 numbers |
| Copy resolution | 600 x 600 dpi | Network protocols | TCP/IP, Net BEUI | One touch dial | 100 numbers |
| Greyscales | 256 | Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2, Linux, Mac ex OS 10.5 | Group dial | 50 numbers |
| Paper feed | 1 x 250 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm]) | Emulations | PCL6 (PCL 5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS | Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 |
| Paper weights | Universal cassette 60-163 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ² | Functions | USB direct printing, e-mail printing, PDF direct printing, private printing, barcode printing, WSD-/Internet printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud Print, Wi-Fi Direct® (only P-3527w MFP) | Functions | Network fax driver, automatic redialling, delayed transmission |
| Paper output | 150 sheet A4 | | | Options | |
| System memory | 512 MB RAM, max 1,536 MB RAM | | | Paper feed | max 2 x PF-1100 (250 sheet universal cassettes [DIN A6R-DIN A4, 60-163 g/m ²]) |
| Continuous copying | 1-999 copies | | | Other options | Card authentication kit (B), UG-33 ThinPrint® kit, cabinet no. 78 |
| Zoom | 25 %-400 % in steps of 1 % | | | | |
| Functions | Touch screen (4.3 inch for P-3527w MFP only), duplex, job reservation, job programs, ID card copy, continuous scan, skip blank pages, N-up, quiet mode (half speed mode), 100 Management codes | | | | |
| | | Scan system | | | |
| | | Scan type | CIS colour and b/w | | |
| | | Scan format | max A4 | | |
| | | Scan speed | b/w: max 40 A4 originals/min, colour: max 23 A4 originals/min with 300 dpi | | |
| | | Scan resolution | 200 dpi, 300 dpi, 400 dpi, 600 dpi | | |
| | | Scan mode | Photo, text, photo/text, OCR | | |
| | | File types | TIFF, JPEG, PDF, high compression PDF, PDF/A-1, XPS | | |
| | | Interfaces | 10/100/1000BaseTX, USB 2.0 | | |
| | | Network protocol | TCP/IP | | |
| | | Operating systems | Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2 | | |
| | | Functions | Scan to SMB, Scan to e-mail, Scan to FTP, Scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP | | |

Dimensions/Weight

| | |
|-------------------|--------------------------------|
| Dimensions | 437 x 417 x 412 mm (H x W x D) |
| Weight | approx. 19 kg |

Environment

| | |
|--------------------------|--|
| Mains voltage | 220/240 V, 50/60 Hz |
| Power consumption | approx. 982 W max, approx. 661 W in operation, approx. 21 W in stand-by mode, approx. 1 W in sleep mode, TEC value: 0.43 Wh/week |

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

www.triumph-adler.com



*Depending on operating status.

Specifications subject to change without notice.

Image shows machine with optional accessories.

TA Triumph-Adler