

Technical Data:



P-4534DN • P-5034DN • P-5534DN • P-6034DN



GENERAL		DIMENSIONS/WEIGHT		PRINT SYSTEM	
Type	Desktop	Dimensions (H x W x D)	P-4534DN: 308 x 390 x 416 mm P-5034DN: 343 x 390 x 416 mm P-5534DN: 343 x 390 x 416 mm P-6034DN: 363 x 410 x 416 mm	Type	Integrated within the system
Function	Print	Weight	P-4534DN: 14.6 kg P-5034DN: 16.1 kg P-5534DN: 16.1 kg P-6034DN: 16.2 kg	Print format	A6R-A4
Print technology	Laser b/w			Print resolution	1,200 x 1,200 dpi
Print speed	P-4534DN: max 45 DIN A4 pages/min, Duplex max. 22.5 DIN A4 pages/min P-5034DN: max 50 DIN A4 pages/min, Duplex max 35.5 DIN A4 pages/min P-5534DN: max 55 DIN A4 pages/min, Duplex max 39.5 DIN A4 pages/min P-6034DN: max 60 DIN A4 pages/min, Duplex max 43 DIN A4 pages/min			Processor	ARM Cortex-A53 Dual Core, 1.4 GHz
1st page	P-4534DN: 5.3 seconds* P-5034DN: 5.4 seconds* P-5534DN: 4.5 seconds* P-6034DN: 4.5 seconds*			Interfaces	USB 2.0, 10/100/1000BaseTX, USB host
Warm-up time	P-4534DN: 16 seconds* P-5034DN: 20 seconds* P-5534DN: 25 seconds* P-6034DN: 25 seconds*			Network protocols	TCP/IP, Net BEUI
Copy resolution	1,200 x 1,200 dpi			Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
Greyscales	256			Emulations	PCL6 (PCL 5e/c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, XPS, Open XPS, PDF 1.7
Paper feed	1 x 500 sheet universal cassette (A6R-A4, min 140 x 148 mm, max 216 x 356 mm)****, multi-bypass: 216 x 356 mm to 70 x 139,7 mm banner length: max 915 mm	Mains voltage	220/240 V, 50 Hz	Display	LCD Display 128x64 dot, 21 character x 5 lines (W/Backlight)
Paper weights	Universal cassette 60-120 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-120 g/m ²	Power consumption	P-4534DN: 1,234 W max, 606 W in operation, 8.4 W in stand-by mode, 0.5 W in sleep-mode, TEC-value: 0.59 KWh/week P-5034DN: 1,247 W max, 652 W in operation, 9 W in stand-by mode, 0.5 W in sleep-mode, TEC-value: 0.67 KWh/week P-5534DN: 1,251 W max, 676.1 W in operation, 9 W in stand-by mode, 0.5 W in sleep-mode, TEC-value: 0.73 KWh/week P-6034DN: 1,258 W max, 710.2 W in operation, 9 W in stand-by mode, 0.5 W in sleep-mode, TEC-value: 0.79 KWh/week	Functions	USB direct printing, printing of e-mails, private printing, barcode printing, WSD/internet printing; Mobile Print/ Apple AirPrint*, Wi-Fi**, Microsoft Universal Print
Paper output	P-4534DN: 250 sheet A4 P-5034DN, P-5534DN, P-6034DN: 500 sheet A4	Noise level	P-4534DN: approx. 50 dB(A) in operation, approx. 30 dB(A) in stand-by mode P-5034DN: approx. 50 dB(A) in operation, approx. 30 dB(A) in stand-by mode P-5534DN: approx. 51 dB(A) in operation, approx. 30 dB(A) in stand-by mode P-6034DN: approx. 52 dB(A) in operation, approx. 33 dB(A) in stand-by mode (ISO 7779/9296)		
System memory	512 MB RAM (max 2.5 GB RAM), 64/256/512 GB SSD**	Safety	GS/TÜV, CE		
Functions	Duplex, job reservation, favourites (programs), quiet mode (half speed mode), Data Security Kit, Secure Boot, Runtime Integrity Check, etc.				

OPTIONS



Other options	Max. 4x PF-3110 (500 sheets universal cassettes), PT-320 output tray (250 sheet face-up, only for 50, 55 & 60 ppm), PF-3100 (2,000 sheets universal cassettes), PB-325 (attachment for PF-3100), IC card reader, Card Authentication Kit (B), UG-33 ThinPrint® Kit, UG-50 (Trusted Platform Module), IB-50 Gigabit Ethernet card, IB-37 (5 GHz) or IB-38 (2.4 GHz)*** WLAN card, HD-17 SSD (64 GB), HD-18 SSD (256 GB), HD-19 SSD (512 GB), MM-20 (1 GB DIMM), MM-21 (2 GB DIMM), cabinet no. 79 (high), cabinet no. 80 (low), CA-3100 Caster Kit
----------------------	---

- * depending on operating status
- ** optional
- *** country-specific
- **** P-4534DN supports only up to A5R

Specifications subject to change without notice.
Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler