

Technical Data: 4009ci • 5009ci • 6009ci • 7009ci

GENERAL	
Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A3
Copy/print speed	4009ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w 5009ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w 6009ci: max 60 A4 pages/min and max 30 A3 pages/min in colour and b/w 7009ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and b/w
1st page (Print/Copy)	Colour: 6.5/5.9 seconds ¹ , b/w: 5.1/ 4.5 seconds* (4009ci), Colour: 5.4/4.8 seconds ¹ , b/w: 4.3/3.7 seconds* (5009ci), Colour: 5.1/4.4 seconds ¹ , b/w: 3.8/ 3.4 seconds* (6009ci), Colour: 5.0/4.4 seconds ¹ , b/w: 3.7/3.4 seconds* (7009ci)
Warm-up time	17 seconds (4009ci/5009ci/6009ci) 26 seconds (7009ci)
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
Paper weights	Universal cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 64-256 g/m ²
Paper output	500 sheet A4
System memory	4 GB RAM, 128 GB SSD/optional: 320 GB or 1 TB HDD ²
Continuous copying	1-9,999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), trusted platform module (TPM), secure boot and runtime integrity check, simple certificate enrollment protocol (SCEP), TLS 1.3, OCSP, CRL, S/MIME, SIEM-Support, Allowlisting, fax server connectivity etc.

DIMENSIONS/WEIGHT	
Dimensions	790 x 602 x 665 mm (H x W x D)
Weight	approx. 95 kg

ENVIRONMENT	
Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,750 W (2,400 W - 7008ci) max, approx. 570/680/850/970 W in operation (4009ci/5009ci/6009ci/7009ci), approx. 45 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.51/0.63/0.79/1.01 kWh/week (4009ci/5009ci/6009ci/7009ci)

Noise level	4009ci/5009ci/6009ci/7009ci: approx. (51.3/50.7) (53.6/52.7) (54.9/54.3) (56.1/55.7) dB(A) in operation (colour / b/w-mode), stand-by mode: 30.9/31.6/33.2/33.9 dB(A) (ISO 7779/9296)
Safety	GS/TÜV, CE
PRINT SYSTEM	
Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi
Processor	ARM A53 1.6GHz
Interfaces	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac os X 10.14
Emulations	PCL6 (Se, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIc
Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct ³

SCAN SYSTEM	
Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 137 (simplex) or 274 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multi crop scan, handwriting enhancement, document guard, cloud capture functionality, image defect prevention, ID-scan

OPTIONAL FAXSYSTEM 12	
Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi

Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS	
Original feeder	DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²), DP-7170 document processor with simultaneous duplex scanning, multi-feed detection and sensor with staple detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7008ci), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7140 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7150 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7140 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 inserter (available for 6009ci/7009ci), ZF-7100 Z-fold unit (available for 6009ci/7009ci)
Job separator	JS-7100 (100 sheet, 52-300 g/m ² , A6R - SRA3), JS-7110 inner shift tray (250 sheet, 52-300 g/m ² , A6R - SRA3)
Paper feed	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (IEEE802.11b/g/n, Wi-Fi direct, WPA3), IB-37 WLAN card (IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD ⁴), HD-16 (1 TB HDD ⁴), Fiery® Controller (Printing System 17)

- ¹ Depending on operating status
- ² For copy, print, scan, fax
- ³ optional
- ⁴ IB-38 is only available for selected countries outside the EU that do not support the IB-37








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.