

Technical Data:

P-4021 MFP • P-4026w MFP • P-4027iw MFP

GENERAL		ENVIRONMENT		Network protocol	
Type	Desktop	Mains voltage	220/240 V, 50(60 Hz)	Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
Function	P-4021 MFP: Copy, print, scan P-4026w MFP/P-4027iw MFP: Copy, print, scan, fax	Power consumption	P-4021 MFP/P-4026w MFP: approx. 1,107 W max, approx. 574 W in operation, approx. 12 W in stand-by mode, approx. 0.4 W in sleep mode, TEC value: 0.35 KWh/week P-4027iw MFP: approx. 1,107 W max, approx. 574 W in operation, approx. 12 W in stand-by mode, approx. 0.4 W in sleep mode, TEC value: 0.35 KWh/week	Functions	Scan to SMB (version 3.0), Scan to E-Mail (SMT>P), Scan to FTP, Scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, Multi Crop function ¹ , eSCL support (ChromeOS scan, AirPrint and Mopria scan)
Print technology	Laser b/w	Noise level	approx. 50.2 dB(A) in operation, not measureable in stand-by mode (ISO 7779/9296)	FAX SYSTEM (P-4026w MFP / P-4027iw MFP)	
Original format	max A4 from platen glass			Compatibility	Super G3
Original feeder	50 sheet document processor with simultaneous duplex scanning			Original format	max A4
	A6R-A4, 50-160 g/m ² (simplex/duplex)	Safety	GS/TÜV, CE	Modem speed	33.6 kbps
Copy/print speed	40 A4 pages/min, duplex: max 20 A4 pages/min	PRINT SYSTEM		Transmission speed	3 seconds or less using JBIG
1st page (print/copy)¹	7.4 sec	Type	Integrated within the system	Compression method	JBIG, MMR, MR, MH
Warm-up time	P-4021 MFP/P-4026w MFP: 19 sec ¹ P-4027iw MFP: 29 sec ¹	Print format	A6R-A4	Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi)
Copy resolution	600 x 600 dpi	Print resolution	600 x 600 dpi, max. 1,200 x 1,200 dpi (reduced speed)	Fax memory	8 MB (6.75 MB image memory)
Greyscales	256	Processor	ARM Cortex-A9 dual core 1.2 GHz + ARM Cortex-M3 100 MHz	Abbreviated dial	300 numbers
Paper feed	1 x 250 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm])	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (1), SD-card slot, Wi-Fi ²	One touch dial	22/100 numbers (P-4026w MFP/P-4027iw MFP)
Paper weights	Universal cassette 60-163 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ²	Network protocols	TCP/IP, Net BEUI	Group dial	50 numbers
Paper output	150 sheets A4	Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
System memory	P-4021 MFP/P-4026w MFP: 1 GB RAM P-4027iw MFP: 2 GB RAM	Emulations	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	Functions	Network fax driver, automatic redialling, delayed transmission
Continuous copying	1-999 copies	SCAN SYSTEM		OPTIONS	
Zoom	25 %-400 % in steps of 1 %	Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/iOS), Apple AirPrint, Universal print, Wi-Fi ²	Paper feed	max 2x PF-1100 (250 sheet universal cassette [A6-A4, 60-163 g/m ²])
Display	P-4021 MFP/P-4026w MFP: LCD display 128 x 64 dots, half size 21 characters x 5 lines with numeric keypad P-4027iw MFP: Full color 4.3-inch LCD with pressure sensitive touch screen panel			Other options	Card authentication kit (B), UG-33 ThinPrint [®] kit, UG-50 Trusted Platform Module, cabinet no. 78
Functions	Duplex, job reservation, job programs, ID-card copy, continuous scan, skip blank pages, N-up-printing, login by function, 100 management codes, Secure Boot ³ , Runtime Integrity Check ³ , Simple Certificate Enrollment Protocol (SCEP), TLS 1.3, OCSP, CRL ⁴ , S/MIME ⁴ SIEM-Support, fax server interface etc.			¹ depending on operating status ² optional ³ UG-50 Trusted Platform Module necessary ⁴ optional SD card memory required	
DIMENSIONS/WEIGHT					
Dimensions (H x W x D)	437 x 417 x 412 mm				
Weight	approx. 19 kg				








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.